
istacpy

Instituto Canario de Estadistica (ISTAC)

May 26, 2021

CONTENTS

1 Installation	3
2 Usage	5
2.1 Indicators	5
2.2 Statistical resources	23
2.3 Structural resources	29
2.4 Error handling	51
Python Module Index	53
Index	55

istacpy is a Python package for obtaining open data from Instituto Canario de Estadística (ISTAC). It provides a wrapper to the [open API catalog](#).

**CHAPTER
ONE**

INSTALLATION

```
pip install istacpy
```


The package is divided into several modules depending on the resource you want to retrieve:

2.1 Indicators

2.1.1 `istacpy.indicators.lite`

This is a lite version of the rest of the indicators API. It's a kind of wrapper to facilitate the access to indicators data. It's not as powerful as the underneath functions but it hides a lot of the business logic of the API, so it's quite suitable to quickly retrieve information.

An indicator is defined by three dimensions: **geographical**, **time** and **measure**. Through this lite submodule the idea is to reduce these dimensions setting a custom user value for each one:

Import the module

First of all, you have to import the right submodule:

```
>>> from istacpy.indicators.lite import indicators
```

Look for subjects

Indicators are grouped in subjects. For this purpose the function `istacpy.indicators.lite.indicators.get_subjects()` is provided. Access easily to these subjects:

```
>>> indicators.get_subjects()
(('011', 'Territorio y usos del suelo'),
 ('012', 'Medio ambiente'),
 ('021', 'Población'),
 ('022', 'Movimiento natural'),
 ('023', 'Movimientos migratorios'),
 ...)
```

Each tuple represents: **subject code** and **subject title**. Subjects are **sorted** by its code.

Look for indicators

For this purpose the function `istacpy.indicators.lite.indicators.get_indicators()` is provided. Look for indicators using a *subject code*:

```
>>> indicators.get_indicators(subject_code='022')
([('DEFUNCIONES', 'Defunciones'),
  ('DEFUNCIONES_HOMBRES', 'Defunciones. Hombres'),
  ('DEFUNCIONES_MUJERES', 'Defunciones. Mujeres'),
  ('MATRIMONIOS_SEXO_DIFERENTE',
   'Matrimonios. Entre cónyuges de diferente sexo'),
  ...])
```

Each tuple represents: **indicator code** and **indicator title**. Indicators are **sorted** by its code. No need to paginate results since all them are retrieved at once.

You can even search for indicators within a certain subject and using a query string. For instance, let's say you want to find out data about births within the subject with code 022:

```
>>> indicators.get_indicators('nacimiento', subject_code='022')
([('NACIMIENTOS', 'Nacimientos'),
  ('NACIMIENTOS_HOMBRES', 'Nacimientos. Hombres'),
  ('NACIMIENTOS_MUJERES', 'Nacimientos. Mujeres'),
  ('TASA_FECUNDIDAD', 'Tasa de fecundidad'),
  ('TASA_FECUNDIDAD_10A14', 'Tasa de fecundidad. De 10 a 14 años'),
  ('TASA_FECUNDIDAD_15A19', 'Tasa de fecundidad. De 15 a 19 años'))]
```

You are not restricted to look for indicators always within a subject. For instance, suppose you need to retrieve data about employment:

```
>>> indicators.get_indicators('empleo')
([('ACCIDENTES_TRABAJO_BAJA', 'Accidentes de trabajo con baja'),
  ('ACCIDENTES_TRABAJO_BAJA_JORNADAS',
   'Accidentes de trabajo con baja. Jornadas no trabajadas'),
  ('AFILIACIONES', 'Afiliaciones a la Seguridad Social'),
  ('AFILIACIONES_AGRICULTURA',
   'Afiliaciones a la Seguridad Social. Agricultura'),
  ('AFILIACIONES_ALOJAMIENTO',
   'Afiliaciones a la Seguridad Social. Servicios de alojamiento'),
  ...])
```

Internationalization

As seen in previous examples, information is retrieved in Spanish. But it's also possible to set English as the default language of this lite indicators module:

```
>>> from istacpy.indicators.lite import i18n
>>> i18n.set_english()
```

Now you can search indicators using english terms and the returned values will (mostly) be also in english. In the next example indicators about *employment* will be looked for:

```
>>> indicators.get_indicators('employment')
('AFILIACIONES_ASALARIADOS',
 'Affiliations to Social Security. Wage employment'),
('AFILIACIONES_ASALARIADOS_HOMBRES',
 'Affiliations to Social Security. Wage employment. Men'),
('AFILIACIONES_ASALARIADOS_MUJERES',
 'Affiliations to Social Security. Wage employment. Women'),
('AFILIACIONES_AUTONOMOS',
 'Affiliations to Social Security. Self-employment'),
('AFILIACIONES_AUTONOMOS_HOMBRES',
 'Affiliations to Social Security. Self-employment. Men'),
...
...
```

It's possible to go back and enable again spanish language using `i18n.set_spanish()`.

Note: Not all data from API is fully translated to English. So please be patient if it's the case for you.

Indicator

Once you have identified which indicator you want to work with, it's time to get it from the API. To accomplish it, you will have to use the *indicator code*. Let's say you are interested in *population*, and more precisely, in the POBLACION indicator:

```
>>> indicator = indicators.get_indicator('POBLACION')

>>> indicator
POBLACION (Population)
```

For this purpose the class `istacpy.indicators.lite.indicators.Indicator` is provided. You can get more information about this indicator using the next method:

```
>>> indicator.info()
- Class: istacpy.indicators.lite.indicators.Indicator
- Indicator code: POBLACION
- Title: Population
- Subject: Not available
- Description: Number of persons according to official population figures, referred to 1red
red January of each year, drawn from the Municipal Population Register
- Geographical granularities: {'COUNTIES': 'C', 'ISLANDS': 'I', 'REGIONS': 'R',
red 'MUNICIPALITIES': 'M'}
- Time granularities: {'YEARLY': 'Y'}
- Measures: {'ABSOLUTE': 'A', 'ANNUAL_PERCENTAGE_RATE': 'N', 'INTERPERIOD_PERCENTAGE_RATE
red ': 'I', 'ANNUAL_PUNTUAL_RATE': 'M', 'INTERPERIOD_PUNTUAL_RATE': 'J'}
- Available years: 2000,2001,2002,2003,2004,2005,2006,2007,2008,2009,2010,2011,2012,2013,
red 2014,2015,2016,2017,2018,2019
```

As you can see, every field contains helpful information:

- *Class*: shows the full qualified name of the indicator.
- *Indicator code*: shows the indicator code and can be also independently accessed through the `code` attribute.

- *Title*: shows the indicator title (internationalized if proceed) and can be also independently accessed through the `title` attribute.
- *Subject*: shows the subject where this indicator is included (internationalized if proceed) and can be also independently accessed through the `subject` attribute.
- *Description*: shows the indicator description (internationalized if proceed) and can be also independently accessed through the `description` attribute.
- *Geographical granularities*: shows the available geographical granularities for this indicator and can be also independently accessed through the `geographical_granularities` attribute. It's a `dict` where `keys` are **granularity codes** and `values` are **granularity ids** (they will be used later).
- *Time granularities*: shows the available time granularities for this indicator and can be also independently accessed through the `time_granularities` attribute. It's a `dict` where `keys` are **granularity codes** and `values` are **granularity ids** (they will be used later).
- *Measures*: shows the available measures for this indicator and can be also independently accessed through the `measures` attribute. It's a `dict` where `keys` are **measure codes** and `values` are **measure ids** (they will be used later).
- *Available years*: shows the available years (as time dimension) for this indicator and can be also independently accessed through the `available_years` attribute. It's a list containing the available years for the different combinations of granularities and measures.

Note: It's possible that some available year has no data for a certain combination of granularities and measures, since `available_years` is just a summary of all possible time slots.

Since this object internally uses an `istacpy.indicators.indicators` method to retrieve data from API, you can always access this information through `indicator.api_response`.

Indicator Data

Once you have inspected our indicator, you are ready to get some data from it. For this purpose the method `istacpy.indicators.lite.indicators.Indicator.get_data()` is provided. Suppose you need to know the evolution of population on every Canary island. Query this through the next sentence:

```
>>> data = indicator.get_data(geo='I')

>>> data
POBLACION (Población)
<2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008, 2009, 2010, 2011, 2012, 2013, 2014, 2015, 2016,
↪ 2017, 2018, 2019>
{'Lanzarote': (96310, 103044, 109942, 114715, 116782, 123039, 127457, 132366, 139506, ↪
↪ 141938, 141437, 142517, 142132, 141953, 141940, 143209, 145084, 147023, 149183, ↪
↪ 152289), 'Fuerteventura': (60124, 66025, 69762, 74983, 79986, 86642, 89680, 94386, ↪
↪ 100929, 103167, 103492, 104072, 106456, 109174, 106930, 107367, 107521, 110299, 113275,
↪ 116886), 'Gran Canaria': (741161, 755489, 771333, 789908, 790360, 802247, 807049, ↪
↪ 815379, 829597, 838397, 845676, 850391, 852225, 852723, 851157, 847830, 845195, 843158,
↪ 846717, 851231), 'Tenerife': (709365, 744076, 778071, 799889, 812839, 838877, 852945, ↪
↪ 865070, 886033, 899833, 906854, 908555, 898680, 897582, 889936, 888184, 891111, 894636,
↪ 904713, 917841), 'La Gomera': (18300, 18990, 19098, 19580, 21220, 21746, 21952, 22259,
↪ 22622, 22769, 22776, 23076, 22350, 21153, 20721, 20783, 20940, 20976, 21136, 21503),
↪ 'La Palma': (82483, 84319, 85547, 85631, 84282, 85252, 86062, 85933, 86528, 86996, ↪
↪ 87324, 87163, 85468, 85115, 83456, 82346, 81486, 81350, 81863, 82671), 'El Hierro': ↪
↪ (8533, 9423, 10002, 10162, 10071, 10477, 10688, 10558, 10753, 10892, 10960, 10995 (next page)
↪ 11033, 10979, 10675, 10587, 10679, 10798, 10968)}
```

(continued from previous page)

For this purpose the class `istacpy.indicators.lite.indicators.IndicatorData` is provided. Get more information about this data using the next method:

```
>>> data.info()
· Class: istacpy.indicators.lite.indicators.IndicatorData
· Indicator code: POBLACION
· Title: Población
· Geographical granularity: ISLANDS
· Time granularity: YEARLY
· Measure: ABSOLUTE
· Index: 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008, 2009, 2010, 2011, 2012, 2013, 2014, 2015,
→ 2016, 2017, 2018, 2019
· Columns: Lanzarote, Fuerteventura, Gran Canaria, Tenerife, La Gomera, La Palma, El Hierro
· Shape: (20, 7)
· Num. observations: 140
```

As you can see, every field contains helpful information:

- *Class*: shows the full qualified name of the indicator data.
- *Indicator code*: shows the indicator code and can be also independently accessed through the `code` attribute.
- *Title*: shows the indicator title (internationalized if proceed) and can be also independently accessed through the `title` attribute.
- *Geographical granularity*: shows the pinned geographical granularity for this dataset and can be also independently accessed through the `geographical_granularity` attribute.
- *Time granularity*: shows the pinned time granularity for this dataset and can be also independently accessed through the `time_granularity` attribute.
- *Measure*: shows the pinned measure for this dataset and can be also independently accessed through the `measure` attribute.
- *Index*: shows the index of the dataset as a tuple of **sorted** years. It can be also independently accessed through the `index` attribute.
- *Columns*: shows the columns of the dataset as a tuple of geographical locations. It can be also independently accessed through the `columns` attribute.
- *Shape*: shows a tuple with index size by columns size and can be also independently accessed through the `shape` attribute.
- *Num. observations*: shows the total number of observations within the dataset and can be also independently accessed through the `num_observations` attribute.

Although data itself is not shown on `info()` calling, it's always available through `.data` attribute:

```
>>> data.data
{'Lanzarote': (96310,
 103044,
 109942,
 114715,
 116782,
 123039,
 127457,
```

(continues on next page)

(continued from previous page)

```

132366,
139506,
141938,
141437,
142517,
142132,
141953,
141940,
143209,
145084,
147023,
149183,
152289),
'Fuerteventura': (60124,
66025,
69762,
...

```

Note: Each indicator is linked to an indicator data. So, you can access extra information through this attribute `data.indicator`.

Since this object internally uses an `istacpy.indicators.indicators` method to retrieve data from API, you can always access this information through `data.api_response`.

Convert to dataframe

In case you are working with `Pandas` it's super easy to convert indicator data to dataframe:

```

>>> data.as_dataframe()
      Lanzarote  Fuerteventura  Gran Canaria  Tenerife  La Gomera  La Palma  El Hierro
2000     96310        60124     741161    709365     18300    82483     8533
2001    103044        66025     755489    744076     18990    84319     9423
2002    109942        69762     771333    778071     19098    85547    10002
2003    114715        74983     789908    799889     19580    85631     10162
2004    116782        79986     790360    812839     21220    84282     10071
2005    123039        86642     802247    838877     21746    85252     10477
2006    127457        89680     807049    852945     21952    86062     10688
2007    132366        94386     815379    865070     22259    85933     10558
2008    139506        100929    829597    886033     22622    86528     10753
2009    141938        103167    838397    899833     22769    86996     10892
2010    141437        103492    845676    906854     22776    87324     10960
2011    142517        104072    850391    908555     23076    87163     10995
2012    142132        106456    852225    898680     22350    85468     11033
2013    141953        109174    852723    897582     21153    85115     10979
2014    141940        106930    851157    889936     20721    83456     10675
2015    143209        107367    847830    888184     20783    82346     10587
2016    145084        107521    845195    891111     20940    81486     10587
2017    147023        110299    843158    894636     20976    81350     10679
2018    149183        113275    846717    904713     21136    81863     10798
2019    152289        116886    851231    917841     21503    82671     10968

```

Important: pip install pandas is a required dependency in case you want to use .as_dataframe() method.

For this purpose the method `istacpy.indicators.lite.indicators.Indicator.as_dataframe()` is provided.

Convert to list

It's also possible to flatten data and get a list of values as follows:

```
>>> data.as_list()
[96310,
 103044,
 109942,
 114715,
 116782,
 123039,
 127457,
 ...
 10979,
 10675,
 10587,
 10587,
 10679,
 10798,
 10968]
```

For this purpose the method `istacpy.indicators.lite.indicators.Indicator.as_list()` is provided.

Default values

If no arguments are given, you will get data with default granularities and measures. More precisely, returned data will use the following **specifications by default**:

- Geographical granularity: will be set by default as the granularity with the largest available grain.
- Time granularity: will be set by default as the granularity with the largest available grain.
- Measure: will be set by default as the absolute measure.

For example, you could get data from *population* indicator as follows (**using default values**):

```
>>> data = indicator.get_data()

>>> data
POBLACION (Población)
<2000,2001,2002,2003,2004,2005,2006,2007,2008,2009,2010,2011,2012,2013,2014,2015,2016,
 ↵2017,2018,2019>
{'Canarias': (1716276, 1781366, 1843755, 1894868, 1915540, 1968280, 1995833, 2025951, ↵
 ↵2075968, 2103992, 2118519, 2126769, 2118344, 2118679, 2104815, 2100306, 2101924, ↵
 ↵2108121, 2127685, 2153389)}
```

Check the used values for granularities and measure as follows:

```
>>> data.geographical_granularity  
'REGIONS'  
  
>>> data.time_granularity  
'YEARLY'  
  
>>> data.measure  
'ABSOLUTE'
```

Query format

One of the most important features of this module is to allow queries in an easy and powerful way. Let's see distinct use cases to demonstrate its capabilities.

A population indicator will be used within the next examples:

```
>>> indicator = indicators.get_indicator('POBLACION')  
  
>>> indicator.info()  
· Class: istacpy.indicators.lite.indicators.Indicator  
· Indicator code: POBLACION  
· Title: Population  
· Subject: Not available  
· Description: Number of persons according to official population figures, referred to 1red  
↳ January of each year, drawn from the Municipal Population Register  
· Geographical granularities: {'REGIONS': 'R', 'ISLANDS': 'I', 'COUNTIES': 'C',  
↳ 'MUNICIPALITIES': 'M'}  
· Time granularities: {'YEARLY': 'Y'}  
· Measures: {'ABSOLUTE': 'A', 'ANNUAL_PERCENTAGE_RATE': 'N', 'INTERPERIOD_PERCENTAGE_RATE': 'I',  
↳ 'ANNUAL_PUNTUAL_RATE': 'M', 'INTERPERIOD_PUNTUAL_RATE': 'J'}  
· Available years: 2000,2001,2002,2003,2004,2005,2006,2007,2008,2009,2010,2011,2012,2013,  
↳ 2014,2015,2016,2017,2018,2019
```

Evolution of population in counties of Tenerife

```
>>> data = indicator.get_data(geo='C|Tenerife')
```

```
>>> data.info()  
· Class: istacpy.indicators.lite.indicators.IndicatorData  
· Indicator code: POBLACION  
· Title: Population  
· Geographical granularity: COUNTIES  
· Time granularity: YEARLY  
· Measure: ABSOLUTE  
· Index: 2000,2001,2002,2003,2004,2005,2006,2007,2008,2009,2010,2011,2012,2013,2014,2015,  
↳ 2016,2017,2018,2019  
· Columns: Tenerife - Área Metropolitana,Tenerife Norte - Acentejo,Tenerife Norte -  
↳ Daute,Tenerife Norte - Icod,Tenerife Norte - Valle de La Orotava,Tenerife Sur - Abona,  
↳ Tenerife Sur - Suroeste,Tenerife Sur - Valle de Güímar  
· Shape: (20, 8)  
· Num. observations: 160
```

Here we used the geo argument (for *geographical granularity*), indicating C for COUNTIES and filtering by *Tenerife*. As we described in *Default values*, measure is set to *absolute* when no value is provided.

Evolution of population in municipalities of Lanzarote and Fuerteventura

```
>>> data = indicator.get_data(geo='M|Lanzarote,Fuerteventura')
```

```
>>> data.info()
- Class: istacpy.indicators.lite.indicators.IndicatorData
- Indicator code: POBLACION
- Title: Population
- Geographical granularity: MUNICIPALITIES
- Time granularity: YEARLY
- Measure: ABSOLUTE
- Index: 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008, 2009, 2010, 2011, 2012, 2013, 2014, 2015,
- Columns: Arrecife, Haría, San Bartolomé, Teguise, Tías, Tinajo, Yaiza, Antigua, Betancuria, La
- Oliva, Pájara, Puerto del Rosario, Tuineje
- Shape: (20, 13)
- Num. observations: 260
```

Here we used the geo argument (for *geographical granularity*), indicating M for MUNICIPALITIES and filtering by *Lanzarote* and *Gran Canaria*. As we described in *Default values*, measure is set to *absolute* when no value is provided.

Comparation of population in counties between 2009 and 2019

```
>>> data = indicator.get_data(geo='C', time='Y|2009:2019')
```

```
>>> data.info()
- Class: istacpy.indicators.lite.indicators.IndicatorData
- Indicator code: POBLACION
- Title: Population
- Geographical granularity: COUNTIES
- Time granularity: YEARLY
- Measure: ABSOLUTE
- Index: 2009, 2010, 2011, 2012, 2013, 2014, 2015, 2016, 2017, 2018, 2019
- Columns: Lanzarote - Este, Lanzarote - Norte, Lanzarote - Suroeste, Fuerteventura -
- Centro, Fuerteventura - Norte, Fuerteventura - Sur, Gran Canaria - Área Metropolitana,
- Gran Canaria Norte - Centro Norte, Gran Canaria Norte - Noroeste, Gran Canaria Norte -
- Oeste, Gran Canaria Sur - Sur, Gran Canaria Sur - Sureste, Tenerife - Área Metropolitana,
- Tenerife Norte - Acentejo, Tenerife Norte - Daute, Tenerife Norte - Icod, Tenerife Norte -
- Valle de La Orotava, Tenerife Sur - Abona, Tenerife Sur - Suroeste, Tenerife Sur - Valle
- de Güímar, La Gomera - Norte, La Gomera - Sur, La Palma - Capitalina, La Palma - Noreste,
- La Palma - Noroeste, La Palma - Valle de Aridane, El Hierro - El Hierro
- Shape: (11, 27)
- Num. observations: 297
```

Here we used the geo argument (for *geographical granularity*), indicating C for COUNTIES and time argument (for *time granularity*), indicating Y for YEARLY and filtering with a range between two years. Range can be either specified with : or -. As we described in *Default values*, measure is set to *absolute* when no value is provided.

Comparation of population in islands between first and last available years

```
>>> data = indicator.get_data(geo='I', time='Y|F,L')
```

```
>>> data.info()
· Class: istacpy.indicators.lite.indicators.IndicatorData
· Indicator code: POBLACION
· Title: Population
· Geographical granularity: ISLANDS
· Time granularity: YEARLY
· Measure: ABSOLUTE
· Index: 2000,2019
· Columns: Lanzarote,Fuerteventura,Gran Canaria,Tenerife,La Gomera,La Palma,El Hierro
· Shape: (2, 7)
· Num. observations: 14
```

Here we used the `geo` argument (for *geographical granularity*), indicating I for ISLANDS and `time` argument (for *time granularity*) filtering by first available year (denoted by F) and last available year (denoted by L). Note that time filter uses a comma indicating separate values. As we described in [Default values](#), measure is set to *absolute* when no value is provided.

Comparation of population in municipalities of La Gomera between 2005-2010 and 2015-last available year

```
>>> data = indicator.get_data(geo='M|La Gomera', time='Y|2005:2010,2015:L')
```

```
>>> data.info()
· Class: istacpy.indicators.lite.indicators.IndicatorData
· Indicator code: POBLACION
· Title: Population
· Geographical granularity: MUNICIPALITIES
· Time granularity: YEARLY
· Measure: ABSOLUTE
· Index: 2005,2006,2007,2008,2009,2010,2015,2016,2017,2018,2019
· Columns: Agulo,Alajeró,Hermigua,San Sebastián de La Gomera,Valle Gran Rey,Vallehermoso
· Shape: (11, 6)
· Num. observations: 66
```

Here we used the `geo` argument (for *geographical granularity*), indicating M for MUNICIPALITIES and filtering by *La Gomera* and `time` argument (for *time granularity*) indicating Y for YEARLY and filtering by the required ranges. Note that L stands for *last available year* and can be used in every expression. As we described in [Default values](#), measure is set to *absolute* when no value is provided.

Evolution of population in counties of Gran Canaria in annual percentage rate

```
>>> data = indicator.get_data(geo='C|Gran Canaria', measure='N')
```

```
>>> data.info()
· Class: istacpy.indicators.lite.indicators.IndicatorData
· Indicator code: POBLACION
· Title: Population
· Geographical granularity: COUNTIES
· Time granularity: YEARLY
· Measure: ANNUAL_PERCENTAGE_RATE
· Index: 2000,2001,2002,2003,2004,2005,2006,2007,2008,2009,2010,2011,2012,2013,2014,2015,
  ↵ 2016,2017,2018,2019
· Columns: Gran Canaria - Área Metropolitana,Gran Canaria Norte - Centro Norte,Gran_
  ↵ Canaria Norte - Noroeste,Gran Canaria Norte - Oeste,Gran Canaria Sur - Sur,Gran_
  ↵ Canaria Sur - Sureste
```

(continues on next page)

(continued from previous page)

- Shape: (20, 6)
- Num. observations: 120

Here we used the geo argument (for *geographical granularity*), indicating C for COUNTIES and filtering by *Gran Canaria* and measure argument (for *measure representation*) indicating N for ANNUAL_PERCENTAGE_RATE. As we described in *Default values*, time is set to *largest grane* when no value is provided.

Evolution of vehicles in circulation in every Canary island with monthly values during the last available year

First of all you have to choose the right indicator:

```
>>> indicator = indicators.get_indicator('PARQUE_VEHICULOS')

>>> indicator.info()
· Class: istacpy.indicators.lite.indicators.Indicator
· Indicator code: PARQUE_VEHICULOS
· Title: National feet of vehicles
· Subject: Not available
· Description: Number of vehicles in circulation according to the fleet prepared by the ↵
    Spanish Traffic Authority. The reference date is the last day of each month
· Geographical granularities: {'REGIONS': 'R', 'ISLANDS': 'I', 'MUNICIPALITIES': 'M'}
· Time granularities: {'YEARLY': 'Y', 'MONTHLY': 'M'}
· Measures: {'ABSOLUTE': 'A', 'ANNUAL_PERCENTAGE_RATE': 'N', 'INTERPERIOD_PERCENTAGE_RATE' ↵
    ': 'I', 'ANNUAL_PUNTUAL_RATE': 'M', 'INTERPERIOD_PUNTUAL_RATE': 'J'}
· Available years: 2005,2006,2007,2008,2009,2010,2011,2012,2013,2014,2015,2016,2017
```

Now you can make the right query:

```
>>> data = indicator.get_data(geo='I', time='M|L')

>>> data.info()
· Class: istacpy.indicators.lite.indicators.IndicatorData
· Indicator code: PARQUE_VEHICULOS
· Title: National feet of vehicles
· Geographical granularity: ISLANDS
· Time granularity: MONTHLY
· Measure: ABSOLUTE
· Index: Jan 2017, Feb 2017, Mar 2017, Apr 2017, May 2017, Jun 2017, Jul 2017, Aug 2017, Sep ↵
    2017, Oct 2017, Nov 2017, Dec 2017
· Columns: Lanzarote, Fuerteventura, Gran Canaria, Tenerife, La Gomera, La Palma, El Hierro
· Shape: (12, 7)
· Num. observations: 84

>>> data
PARQUE_VEHICULOS (National feet of vehicles)
<Jan 2017, Feb 2017, Mar 2017, Apr 2017, May 2017, Jun 2017, Jul 2017, Aug 2017, Sep 2017, Oct ↵
    2017, Nov 2017, Dec 2017>
{'Lanzarote': (119405, 119707, 120112, 120313, 120913, 121656, 122850, 123042, 123401, ↵
    123774, 124536, 125137), 'Fuerteventura': (81898, 82203, 82561, 82748, 83077, 83444, ↵
    83851, 84170, 84499, 84949, 85208, 85485), 'Gran Canaria': (607174, 608634, 610313, ↵
    610878, 612377, 614437, 617703, 619479, 621736, 625164, 626967, 628259), 'Tenerife': ↵
    (687245, 689104, 691208, 693475, 695655, 697987, 700952, 702968, 704847, 706923, ↵
    709383, 710869), 'La Gomera': (14627, 14666, 14684, 14715, 14742, 14771, 14798, 14808, ↵
    14838, 14893, 14956, 14984), 'La Palma': (67895, 68034, 68205, 68362, 68532, 68737, ↵
    68871, 69037, 69200, 69443, 69679, 69652), 'El Hierro': (8180, 8203, 8218, 8250, 8262, ↵
    8286, 8325, 8345, 8378, 8402, 8442, 8451)}
```

(continued from previous page)

Here we used the `geo` argument (for *geographical granularity*), indicating `I` for `ISLANDS` and `time` argument (for *time granularity*), indicating `M` for `MONTHLY` and filtering by `L` (for the *last available year*). As we described in [Default values](#), measure is set to *absolute* when no value is provided.

Automatic conversion of data

API essentially returns string data. This lite module converts values to its proper numeric representation (`int` or `float`). Besides, it handles possible `NaN` values (*not a number*) when conversion is not possible.

This feature can be illustrated through a *sales of cement* indicator. Let's retrieve some data:

```
>>> indicator = indicators.get_indicator('CEMENTO_VENTAS')

>>> indicator
CEMENTO_VENTAS (Wholesale of cement)

>>> data = indicator.get_data()
```

Let's take a look of the API response:

```
>>> data.api_response['observation']
['562199.2',
 '587198.8',
 '527980.0',
 '508627.2',
 '498687.5',
 '451703.5',
 '440478.3',
 '517181.9',
 '678307.4',
 '819994.0',
 '.']
```

You can see that values are *strings* and a *dot* is also in the list. These values are correctly handled by the lite module, converting them to numeric types and identifying `NaN` observations:

```
>>> data
CEMENTO_VENTAS (Wholesale of cement)
<2009, 2010, 2011, 2012, 2013, 2014, 2015, 2016, 2017, 2018, 2019>
{'Canarias': ('NaN', 819994.0, 678307.4, 517181.9, 440478.3, 451703.5, 498687.5, 508627.
˓→2, 527980.0, 587198.8, 562199.2)}
```

Automatic conversion from multiplying units

There are some indicators whose response from API is based on **multiplying units**, that is, returned values must be multiplied by this factor to get the real ones.

This module converts automatically these values to stop worrying about factors.

For example, if you are working with *unemployed population*, this indicator has a *thousands* multiplying unit. Let's see how this automatic conversion works:

```
>>> indicator = indicators.get_indicator('POBLACION_PARADA')

>>> indicator.info()
. Class: istacpy.indicators.lite.indicators.Indicator
. Indicator code: POBLACION_PARADA
. Title: Unemployed population
. Subject: Not available
. Description: Persons aged 16 years and more without work, available to start work and had actively sought work
. Geographical granularities: {'REGIONS': 'R', 'ISLANDS': 'I', 'COUNTIES': 'C'}
. Time granularities: {'QUARTERLY': 'Q'}
. Measures: {'ABSOLUTE': 'A', 'ANNUAL_PERCENTAGE_RATE': 'N', 'INTERPERIOD_PERCENTAGE_RATE': 'I', 'ANNUAL_PUNTUAL_RATE': 'M', 'INTERPERIOD_PUNTUAL_RATE': 'J'}
. Available years: 2002,2003,2004,2005,2006,2007,2008,2009,2010,2011,2012,2013,2014,2015,2016,2017,2018,2019,2020

>>> data = indicator.get_data()
```

Let's compare the last three values of `data` against the last three raw values from API response:

```
>>> data.api_response['observation'][-3:][-1]
['7.62', '9.66', '9.87']

>>> values = data.asList()
>>> values[:3]
[7620.0, 9660.0, 9870.0]
```

You can check that values are correctly converted.

Getting raw codes

By default, the `.get_data()` method provides titles for `index` and `columns` (when possible). This behaviour can be changed if you specify `=` as a prefix on the query string (for each dimension).

Query in a “normal” way:

```
>>> indicator = indicators.get_indicator('POBLACION')

>>> data = indicator.get_data(geo='I')

>>> data.columns
('Lanzarote',
 'Fuerteventura',
 'Gran Canaria',
```

(continues on next page)

(continued from previous page)

```
'Tenerife',
'La Gomera',
'La Palma',
'El Hierro')
```

Query indicating to return raw codes:

```
>>> indicator = indicators.get_indicator('POBLACION')

>>> data = indicator.get_data(geo='=I')

>>> data.columns
('ES708', 'ES704', 'ES705', 'ES709', 'ES706', 'ES707', 'ES703')
```

Note: This can be used in time dimension as well.

API Reference

Functions

Indicator

IndicatorData

2.1.2 istacpy.indicators.geographic

```
istacpy.indicators.geographic.get_indicators_geographic_granularities()
```

Get geographic granularities

This function returns a list of geographic granularities treated in the ISTAC-indicators database. For example provincial, insular or municipal granularity.

Examples

```
>>> get_indicators_geographic_granularities()
```

```
istacpy.indicators.geographic.get_indicators_geographical_values(geographicalgranularitycode,
                                                               subjectcode='', systemcode='')
```

Get geographical values

This function returns values of a geographical granularity that in turn are part of a specific theme or system of indicators.

Parameters

- **geographicalgranularitycode** (*string*) – geographical granularity code
- **subjectcode** (*string*) – subject code
- **systemcode** (*string*) – system code

Examples

```
>>> get_indicators_geographical_values("REGIONS")
>>> get_indicators_geographical_values(
...     "REGIONS",
...     subjectcode="051",
...     systemcode="C00067A"
)
```

`istacpy.indicators.geographic.get_indicators_subjects()`

Get subjects

This function returns all subjects which the ISTAC classifies its statistical operations.

Examples

```
>>> get_indicators_subjects()
```

`istacpy.indicators.geographic.get_indicators_time_granularities()`

Get time granularities

This function returns a list of temporary granularity treated in the ISTAC data bank-indicators ordered from highest to lowest granularity. For example annual, quarterly or monthly granularity.

Examples

```
>>> get_indicators_time_granularities()
```

2.1.3 istacpy.indicators.indicators

Example 1: Get a list of all available indicators:

```
from istacpy.indicators import indicators
indicators.get_indicators()
```

Example 2: Get a list of geographic granularities treated in the ISTAC-indicators database. For example provincial, insular or municipal granularity:

```
from istacpy.indicators import geographic
geographic.get_indicators_geographic_granularities()
```

`istacpy.indicators.indicators.get_indicators(q="", order="", limit=25, offset=0, fields="", representation="")`

Get indicators

This function returns a list of indicators published in the ISTAC-indicators database. An indicator is a measure used to know the intensity of a phenomenon in spacetime. This measure can refer to different spatial or temporal granularities.

Parameters

- `q (string)` – Metadata query on which the searches can be built using `id`, `subjectCode` or `geographicValue`.

- **order** (*string*) – Order. Possible values are: `update` and `id`. Order criteria are ASC and DESC.
- **limit** (*int*) – Results limit. By default `limit = 25`.
- **offset** (*int*) – Displacement. Result from which it is returned. By default `offset = 0`.
- **fields** (*string*) – Use of the answer by adding new fields. Possible values are: `+metadata`, `+data` and `+observationsMetadata`.
- **representation** (*string*) – Allows filtering the observations by their value. Its use only makes sense when `+data` and/or `+observationsMetadata` has been included.

Examples

```
>>> get_indicators(  
...     q='id IN ("AFILIACIONES", "EMPLEO_REGISTRADO_AGRICULTURA")',  
...     order="id ASC",  
...     fields="+data",  
...     representation="GEOGRAPHICAL[35003|35005], MEASURE[ABSOLUTE]"  
... )
```

`istacpy.indicators.indicators.get_indicators_code(indicatorcode)`

Get indicators code

This function returns the metadata that describe the characteristics of a specific indicator, allowing the compression of the measured fact; also through the data request the complete data (for all spacetime) of the indicator is provided.

Parameters `indicatorcode` (*string*) – an indicator code

Examples

```
>>> get_indicators_code("AFILIACIONES")  
>>> get_indicators_code("PARO_REGISTRADO")
```

`istacpy.indicators.indicators.get_indicators_code_data(indicatorcode, representation="", granularity="", fields="")`

Get indicators code data

This function returns complete data (for all spacetime) of the indicator. On the other hand, metadata describing the characteristics of a specific indicator are offered through the metadata request, allowing the compression of the measured fact.

Parameters

- **indicatorcode** (*string*) – an indicator code
- **representation** (*string*) – Allows filtering the observations by their value.
- **granularity** (*string*) – Allows to filter the observations through the granularities of the same.
- **fields** (*string*) – Allows you to customize the response by excluding fields. The possible values are: `-observationsMetadata`.

Examples

```
>>> get_indicators_code_data("AFILIACIONES")
```

2.1.4 istacpy.indicators.systems

`istacpy.indicators.systems.get_indicators_systems(limit=25, offset=0)`

Get indicators systems

This function returns a list of indicator systems published in the ISTAC-indicators database. The indicators are simple or compound statistics, however a single indicator can rarely provide useful information about complex phenomena such as the economic situation, living conditions, schooling or others. Indicator systems are generally designed to generate more and more accurate information about the conditions of a phenomenon; and for this they are organized in dimensions or areas of analysis, under which the indicators are integrated.

Parameters

- **limit** (*int*) – Results limit. By default `limit = 25`.
- **offset** (*int*) – Displacement. Result from which it is returned. By default `offset = 0`.

Examples

```
>>> get_indicators_systems()
```

`istacpy.indicators.systems.get_indicators_systems_code(indicatorSystemCode)`

Get indicators system code

This function returns metadata of a system of indicators published in the ISTAC-indicators database. The indicators are simple or compound statistics, however a single indicator can rarely provide useful information about complex phenomena such as the economic situation, living conditions, schooling or others.

Parameters `indicatorSystemCode` (*string*) – an indicator system code

Examples

```
>>> get_indicators_systems_code("C00075H")
```

`istacpy.indicators.systems.get_indicators_systems_code_instances(indicatorSystemCode, q="", order="", limit=25, offset=0, fields="", representation="", granularity="")`

Get indicators system code instances

This function returns instances of indicators associated with a specific indicator system. An instance of an indicator is nothing more than a spatio-temporal query of an indicator when it is incorporated into a specific indicator system.

Parameters

- **indicatorSystemCode** (*string*) – with an indicator system code
- **q** (*string*) – Query of metadata on which the searches can be built are: `id` and `geographicalValue`.

- **order** (*string*) – Order. Possible values are: `update` and `id` and order criteria are `ASC` and `DESC`.
- **limit** (*int*) – Results limit. By default `limit = 25`.
- **offset** (*int*) – Displacement. Result from which it is returned. By default `offset = 0`.
- **fields** (*string*) – Use of the answer by adding new fields. Possible values are: `+metadata`, `+data` and `+observationsMetadata`.
- **representation** (*string*) – Allows filtering the observations by their value. Its use only makes sense when `+data` and/or `+observationsMetadata` has been included.
- **granularity** (*string*) – Allows to filter the observations through the granularities of the same. Its use only makes sense when `+data` and/or `+observationsMetadata` has been included.

Examples

```
>>> get_indicators_systems_code_instances("C00075H")
>>> get_indicators_systems_code_instances(
...     "C00075H",
...     q='id EQ "INDICADORES_MUNICIPALES"'
... )
```

`istacpy.indicators.systems.get_indicators_systems_code_instances_code(indicatorSystemCode, indicatorInstanceCode)`

Get indicators system code instances code

This function returns metadata of an indicator set associated with a specific indicator system. An instance of an indicator is nothing more than a spatio-temporal query of an indicator when it is incorporated into a specific indicator system.

Parameters

- **indicatorSystemCode** (*string*) –
- **indicatorInstanceCode** (*string*) –

Examples

```
>>> get_indicators_systems_code_instances_code(
...     "C00075H",
...     "21af0477-d63b-493b-ad02-4ab181547223"
... )
```

`istacpy.indicators.systems.get_indicators_systems_code_instances_code_data(indicatorSystemCode, indicatorInstanceCode, representation='', granularity='', fields=')`

Get indicators system code instances code data

This function returns data of an indicator unit associated with a specific indicator system. An instance of an indicator is nothing more than a spatio-temporal query of an indicator when it is incorporated into a specific indicator system.

Parameters

- **indicatorsystemcode** (*string*) – Indicator system code
- **indicatorinstancecode** (*string*) – Indicator instance code
- **representation** (*string*) – Allows filtering the observations by their value.
- **granularity** (*string*) – Allows to filter the observations through the granularities of the same.
- **fields** (*string*) – Allows you to customize the response by excluding fields. The possible values are: -observationsMetadata.

Examples

```
>>> get_indicators_systems_code_instances_code_data(
...     "C00075H",
...     "21af0477-d63b-493b-ad02-4ab181547223"
... )
```

2.2 Statistical resources

2.2.1 Dataframe handling

Apart from all the functions below, there are **two special calls** we can use in order to get a `pandas DataFrame` instead of the usual json API response:

- `istacpy.statisticalresources.queries.get_statisticalresources_queries_agency_resource()`
- `istacpy.statisticalresources.cubes.get_statisticalresources_datasets_agency_resource_version()`

Important: `pip install pandas` is required for this feature to work.

Guess you are looking for data about population under 18 in Canary Islands regarding its employment status. Once you get the *resource identifier* you could make this query:

```
>>> from istacpy.statisticalresources import queries

>>> response = queries.get_statisticalresources_queries_agency_resource(
...     agencyid='ISTAC',
...     resourceid='C00086B_000006',
...     as_dataframe=True
... )

>>> type(response)
istacpy.services.ResolvedAPIResponse
```

Note: Adding the parameter `as_dataframe=True` makes you get a `ResolvedAPIResponse` object.

This object provides two attributes: `dataframe` and `codelists`:

```
>>> response.dataframe
```

	MEDIDAS	TIME_PERIOD	SEXO	SITUACION_ECONOMICA_ICC	VALORACION
0	POBLACION	2018-Q4	_T	ACTUAL_BUSQUEDA_EMPLEO	_T
1	POBLACION	2018-Q4	_T	ACTUAL_BUSQUEDA_EMPLEO	IGUAL
2	POBLACION	2018-Q4	_T	ACTUAL_BUSQUEDA_EMPLEO	MEJOR
3	POBLACION	2018-Q4	_T	ACTUAL_BUSQUEDA_EMPLEO	PEOR
4	POBLACION	2018-Q4	_T	EXPECTATIVA_BUSQUEDA_EMPLEO	_T
..
283	POBLACION__PORCENTAJE	2020-Q4	M	ACTUAL_BUSQUEDA_EMPLEO	PEOR
284	POBLACION__PORCENTAJE	2020-Q4	M	EXPECTATIVA_BUSQUEDA_EMPLEO	_T
285	POBLACION__PORCENTAJE	2020-Q4	M	EXPECTATIVA_BUSQUEDA_EMPLEO	IGUAL
286	POBLACION__PORCENTAJE	2020-Q4	M	EXPECTATIVA_BUSQUEDA_EMPLEO	MEJOR
287	POBLACION__PORCENTAJE	2020-Q4	M	EXPECTATIVA_BUSQUEDA_EMPLEO	PEOR

[288 rows x 6 columns]

```
>>> response.codelists
```

```
{'MEDIDAS': {'POBLACION': 'Población',
 'POBLACION__PORCENTAJE': 'Población. Porcentaje'},
 'TIME_PERIOD': {'2020-Q4': '2020 Cuarto trimestre',
 '2020-Q2': '2020 Segundo trimestre',
 '2019-Q4': '2019 Cuarto trimestre',
 '2019-Q2': '2019 Segundo trimestre',
 '2019-Q1': '2019 Primer trimestre',
 '2018-Q4': '2018 Cuarto trimestre'},
 'SEXO': {'_T': 'Ambos性', 'M': 'Hombres', 'F': 'Mujeres'},
 'SITUACION_ECONOMICA_ICC': {'ACTUAL_BUSQUEDA_EMPLEO': 'Situación actual para encontrar o mejorar un puesto de trabajo',
 'EXPECTATIVA_BUSQUEDA_EMPLEO': 'Expectativa futura para encontrar o mejorar un puesto de trabajo'},
 'VALORACION': {'_T': 'Total',
 'MEJOR': 'Mejor',
 'IGUAL': 'Igual',
 'PEOR': 'Peor'}}}
```

Important: Codelists are mappings between codes and text descriptions. The returned `response.codelists` always contains **spanish texts** because they are most cases.

Recoding of downloaded dataset is as easy as:

```

>>> response.dataframe.replace(response.codelists)
          MEDIDAS      TIME_PERIOD      SEXO
SITUACION_ECONOMICA_ICC VALORACION OBSERVACIONES
0           Población 2018 Cuarto trimestre Ambos sexos Situación actual para...
    ↵encontrar o mejorar un p... Total 1791633
1           Población 2018 Cuarto trimestre Ambos sexos Situación actual para...
    ↵encontrar o mejorar un p... Igual 782350
2           Población 2018 Cuarto trimestre Ambos sexos Situación actual para...
    ↵encontrar o mejorar un p... Mejor 272479
3           Población 2018 Cuarto trimestre Ambos sexos Situación actual para...
    ↵encontrar o mejorar un p... Peor 736804
4           Población 2018 Cuarto trimestre Ambos sexos Expectativa futura para...
    ↵encontrar o mejorar un... Total 1791633
...
...
283 Población. Porcentaje 2020 Cuarto trimestre Hombres Situación actual para...
    ↵encontrar o mejorar un p... Peor 87.10
284 Población. Porcentaje 2020 Cuarto trimestre Hombres Expectativa futura para...
    ↵encontrar o mejorar un... Total 100.00
285 Población. Porcentaje 2020 Cuarto trimestre Hombres Expectativa futura para...
    ↵encontrar o mejorar un... Igual 19.25
286 Población. Porcentaje 2020 Cuarto trimestre Hombres Expectativa futura para...
    ↵encontrar o mejorar un... Mejor 19.35
287 Población. Porcentaje 2020 Cuarto trimestre Hombres Expectativa futura para...
    ↵encontrar o mejorar un... Peor 61.40

[288 rows x 6 columns]

```

Tip: This process can also be made for statistical datasets.

2.2.2 istacpy.statisticalresources.queries

```
istacpy.statisticalresources.queries.get_statisticalresources_queries(lang='es', limit=25,
                                                                    offset=0, orderby='',
                                                                    query='')
```

Get queries

This function allows consulting all existing statistical queries.

Parameters

- **lang (string)** – Language in which you want to get the answer.
- **limit (int)** – Results limit. By default **limit=25**.
- **offset (int)** – Displacement. Result from which it is returned. By default **offset=0**.
- **orderby (string)** – Order. Possible values are ID ASC or ID DESC,
- **query (string)** – Metadata query on which the searches can be built.

Examples

```
>>> get_statisticalresources_queries()
```

```
istacpy.statisticalresources.queries.get_statisticalresources_queries_agency(agencyid,
                                                                           lang='es',
                                                                           limit=25,
                                                                           offset=0,
                                                                           orderby="",
                                                                           query="")
```

Get queries (agencyID)

This function allows to consult all the queries maintained by a certain organization.

Parameters

- **agencyid** (*string*) – Identifier of the maintainer organization of the resource. A possible value is ISTAC.
- **lang** (*string*) – Language in which you want to get the answer.
- **limit** (*int*) – Results limit. By default **limit=25**.
- **offset** (*int*) – Displacement. Result from which it is returned. By default **offset=0**.
- **orderby** (*string*) – Order. Possible values are ID ASC or ID DESC,
- **query** (*string*) – Metadata query on which the searches can be built.

Examples

```
>>> get_statisticalresources_queries_agency(agencyid="ISTAC")
```

```
istacpy.statisticalresources.queries.get_statisticalresources_queries_agency_resource(agencyid,
                                                                                      re-
                                                                                      sour-
                                                                                      ceid,
                                                                                      fields="",
                                                                                      lang='es',
                                                                                      as_dataframe=False)
```

Get queries (agencyID / resourceId)

This function allows to obtain final data of a statistical query with a certain identifier and that also maintains a certain organization.

Parameters

- **agencyid** (*string*) – Identifier of the maintainer organization of the resource. A possible value is ISTAC.
- **resourceid** (*string*) – Resource identifier. A possible value is C00010A_000002.
- **fields** (*string*) – Allows you to customize the response by excluding fields from it. The possible values are -metadata and -data.
- **lang** (*string*) – Language in which you want to get the answer.
- **as_dataframe** (*bool*) – If True, this function returns a namedtuple with: - dataframe: pandas dataframe built from API response. - codelists: mapping between codes and representations for each column.

Examples

```
>>> get_statisticalresources_queries_agency_resource(
...     agencyid="ISTAC",
...     resourceid="C00017A_000001"
... )
```

2.2.3 istacpy.statisticalresources.cubes

`istacpy.statisticalresources.cubes.get_statisticalresources_datasets(lang='es', limit=25, offset=0, orderby='', query='')`

Get datasets

This function allows consulting all existing statistical data cubes.

Parameters

- **lang** (*string*) – Language in which you want to get the answer.
- **limit** (*int*) – Results limit. By default `limit=25`.
- **offset** (*int*) – Displacement. Result from which it is returned. By default `offset=0`.
- **orderby** (*string*) – Order. Possible values are ID ASC or ID DESC,
- **query** (*string*) – Metadata query on which the searches can be built.

Examples

```
>>> get_statisticalresources_datasets()
```

`istacpy.statisticalresources.cubes.get_statisticalresources_datasets_agency(agencyid, lang='es', limit=25, offset=0, orderby='', query='')`

Get datasets (agencyID)

This function allows to consult all the data sets maintained by a certain organization.

Parameters

- **agencyid** (*string*) – Identifier of the maintainer organization of the resource. A possible value is ISTAC.
- **lang** (*string*) – Language in which you want to get the answer.
- **limit** (*int*) – Results limit. By default `limit=25`.
- **offset** (*int*) – Displacement. Result from which it is returned. By default `offset=0`.
- **orderby** (*string*) – Order. Possible values are ID ASC or ID DESC,
- **query** (*string*) – Metadata query on which the searches can be built.

Examples

```
>>> get_statisticalresources_datasets_agency(agencyid="ISTAC")
```

```
istacpy.statisticalresources.cubes.get_statisticalresources_datasets_agency_resource(agencyid,
re-
sour-
ceid,
lang='es',
limit=25,
off-
set=0,
or-
derby='',
query='')
```

Get datasets (agencyID / resourceID)

This function allows to obtain all the versions of a statistical cube with a certain identifier and that also maintains a certain organization.

Parameters

- **agencyid** (*string*) – Identifier of the maintainer organization of the resource. A possible value is ISTAC.
- **resourceid** (*string*) – Resource identifier. A possible value is C00010A_000002.
- **lang** (*string*) – Language in which you want to get the answer.
- **limit** (*int*) – Results limit. By default limit=25.
- **offset** (*int*) – Displacement. Result from which it is returned. By default offset=0.
- **orderby** (*string*) – Order. Possible values are ID ASC or ID DESC,
- **query** (*string*) – Metadata query on which the searches can be built.

Examples

```
>>> get_statisticalresources_datasets_agency_resource(
...     agencyid="ISTAC",
...     resourceid="C00010A_000002"
... )
```

```
istacpy.statisticalresources.cubes.get_statisticalresources_datasets_agency_resource_version(agencyid,
re-
sour-
ceid,
ver-
sion,
dim='',
fields='',
lang='es',
as_dataframe=True)
```

Get datasets (agencyID / resourceID / version)

This function allows to obtain all the versions of a statistical cube with a certain identifier and that also maintains a certain organization.

Parameters

- **agencyid** (*string*) – Identifier of the maintainer organization of the resource. A possible value is ISTAC.
- **resourceid** (*string*) – Resource identifier. A possible value is C00010A_000002.
- **version** (*string*) – Resource version. A possible value is 001.000.
- **dim** (*string*) – Allows filtering the data obtained in the response. A example is TIME_PERIOD:2009|2010.
- **fields** (*string*) – Allows you to customize the response by excluding fields from it. The possible values are -metadata and -data.
- **lang** (*string*) – Language in which you want to get the answer.
- **as_dataframe** (*bool*) – If True, this function returns a namedtuple with: - dataframe: pandas dataframe built from API response. - codelists: mapping between codes and representations for each column.

Examples

```
>>> get_statisticalresources_datasets_agency_resource_version(
...     agencyid="ISTAC",
...     resourceid="C00010A_000002",
...     version="001.000"
... )
```

2.3 Structural resources

Example 1: Get a list of classifications:

```
from istacpy.structuralresources import classifications
classifications.get_structuralresources_codelists()
```

Example 2: Get a list of geographic coordinate from Icod de los Vinos:

```
from istacpy.structuralresources import variables
variables.get_structuralresources_geoinfo('VR_TERRITORIO', 'MUN_ICOD_VINOS')
```

2.3.1 istacpy.structuralresources.category

```
istacpy.structuralresources.category.get_structuralresources_categorisations(limit=25,
                                                                           offset=0,
                                                                           query="",
                                                                           orderby="")
```

Get categorisations

This function returns the content from /v1.0/categorisations

Parameters

- **limit** (*int*) – Results limit. By default limit = 25.

- **offset** (*int*) – Displacement. Result from which it is returned. By default **offset** = 0.
- **query** (*string*) – Query to filter the results.
- **orderby** (*string*) – Field by which to sort the results.

Examples

```
>>> get_structuralresources_categorisations()
>>> get_structuralresources_categorisations(
...     query="ID EQ 2090",
...     orderby="ID ASC"
... )
```

```
istacpy.structuralresources.category.get_structuralresources_categorisations_agency(agencyid,
limit=25,
off-
set=0,
query='',
or-
derby='')
```

Get categorisations agency

This function returns the content from /v1.0/categorisations/{agencyID}

Parameters

- **agencyid** (*string*) – Identifier of the agency that publishes.
- **limit** (*int*) – Results limit. By default **limit** = 25.
- **offset** (*int*) – Displacement. Result from which it is returned. By default **offset** = 0.
- **query** (*string*) – Query to filter the results.
- **orderby** (*string*) – Field by which to sort the results.

Examples

```
>>> get_structuralresources_categorisations_agency("ISTAC")
```

```
istacpy.structuralresources.category.get_structuralresources_categorisations_agency_resource(agencyid,
re-
sour-
ceid,
limit=25,
off-
set=0,
query='',
or-
derby='')
```

Get categorisations agency resource

This function returns the content from /v1.0/categorisations/{agencyID}/{resourceID}

Parameters

- **agencyid** (*string*) – Identifier of the agency that publishes.

- **resourceid** (*string*) – Resource identifier.
- **limit** (*int*) – Results limit. By default **limit** = 25.
- **offset** (*int*) – Displacement. Result from which it is returned. By default **offset** = 0.
- **query** (*string*) – Query to filter the results.
- **orderby** (*string*) – Field by which to sort the results.

Examples

```
>>> get_structuralresources_categorisations_agency_resource("ISTAC", "cat2")
```

```
istacpy.structuralresources.category.get_structuralresources_categorisations_agency_resource_version(agency_id="ISTAC", resource_id="cat2", version="01.000")
```

Get categorisations agency resource version

This function returns the content from /v1.0/categorisations/{agencyID}/{resourceID}/{version}

Parameters

- **agencyid** (*string*) – Identifier of the agency that publishes.
- **resourceid** (*string*) – Resource identifier.
- **version** (*string*) – Specific version of the resource.

Examples

```
>>> get_structuralresources_categorisations_agency_resource_version(
    agency_id="ISTAC",
    resource_id="cat2",
    version="01.000"
)
```

```
istacpy.structuralresources.category.get_structuralresources_categorisations_agency_resource_version(limit=25, offset=0, query="", orderby="")
```

Get category schemes

This function returns the content from /v1.0/categoryschemes

Parameters

- **limit** (*int*) – Results limit. By default **limit** = 25.
- **offset** (*int*) – Displacement. Result from which it is returned. By default **offset** = 0.
- **query** (*string*) – Query to filter the results.
- **orderby** (*string*) – Field by which to sort the results.

Examples

```
>>> get_structuralresources_category_schemes()  
>>> get_structuralresources_category_schemes(  
...     query="ID EQ 2090",  
...     orderby="ID ASC"  
... )
```

```
istacpy.structuralresources.category.get_structuralresources_category_schemes_agency(agencyid,  
                                     limit=25,  
                                     off-  
                                     set=0,  
                                     query='',  
                                     or-  
                                     derby='')
```

Get category schemes agency

This function returns the content from /v1.0/categoryschemas/{agencyID}

Parameters

- **agencyid** (*string*) – Identifier of the agency that publishes.
- **limit** (*int*) – Results limit. By default limit = 25.
- **offset** (*int*) – Displacement. Result from which it is returned. By default offset = 0.
- **query** (*string*) – Query to filter the results.
- **orderby** (*string*) – Field by which to sort the results.

Examples

```
>>> get_structuralresources_category_schemes_agency(  
...     "ISTAC",  
...     query="ID EQ 2090",  
...     orderby="ID ASC"  
... )
```

```
istacpy.structuralresources.category.get_structuralresources_category_schemes_agency_resource(agencyid,  
                                         re-  
                                         sour-  
                                         ceid,  
                                         limit=25,  
                                         off-  
                                         set=0,  
                                         query='',  
                                         or-  
                                         derby='')
```

Get category schemes agency resource

This function returns the content from /v1.0/categoryschemas/{agencyID}/{resourceID}

Parameters

- **agencyid** (*string*) – Identifier of the agency that publishes.
- **resourceid** (*string*) – Resource identifier.

- **limit** (*int*) – Results limit. By default **limit** = 25.
- **offset** (*int*) – Displacement. Result from which it is returned. By default **offset** = 0.
- **query** (*string*) – Query to filter the results.
- **orderby** (*string*) – Field by which to sort the results.

Examples

```
>>> get_structuralresources_category_schemes_agency_resource(
...     "ISTAC",
...     "TEMAS_CANARIAS"
... )
```

istacpy.structuralresources.category.get_structuralresources_category_schemes_agency_resource_version(*agencyid*,
resourceid,
version)

Get category schemes agency resource version

This function returns the content from /v1.0/categorieschemes/{agencyID}/{resourceID}/{version}

Parameters

- **agencyid** (*string*) – Identifier of the agency that publishes.
- **resourceid** (*string*) – Resource identifier.
- **version** (*string*) – Specific version of the resource.

Examples

```
>>> get_structuralresources_category_schemes_agency_resource_version(
...     "ISTAC",
...     "TEMAS_CANARIAS",
...     "01.000"
... )
```

istacpy.structuralresources.category.get_structuralresources_category_schemes_agency_resource_version(*agencyid*,
resourceid,
version)

Get category schemes agency resource version categories

This function returns the content from /v1.0/categorieschemes/{agencyID}/{resourceID}/{version}/categories

Parameters

- **agencyid** (*string*) – Identifier of the agency that publishes.
- **resourceid** (*string*) – Resource identifier.
- **version** (*string*) – Specific version of the resource.
- **limit** (*int*) – Results limit. By default **limit** = 25.
- **offset** (*int*) – Displacement. Result from which it is returned. By default **offset** = 0.
- **query** (*string*) – Query to filter the results.
- **orderby** (*string*) – Field by which to sort the results.

Examples

```
>>> get_structuralresources_category_schemes_agency_resource_version_categories(  
...     "ISTAC",  
...     "TEMAS_CANARIAS",  
...     "01.000"  
... )
```

```
istacpy.structuralresources.category.get_structuralresources_category_schemes_agency_resource_version_c
```

Get category schemes agency resource version categories (id)

This function returns the content from /v1.0/categorieschemes/{agencyID}/{resourceID}/{version}/categories/{categoryID}

Parameters

- **agencyid** (*string*) – Identifier of the agency that publishes.
- **resourceid** (*string*) – Resource identifier.
- **version** (*string*) – Specific version of the resource.
- **categoryid** (*string*) – category identifier

Examples

```
>>> get_structuralresources_category_schemes_agency_resource_version_categories_id(
...     "ISTAC",
...     "TEMAS_CANARIAS",
...     "01.000",
...     "060"
... )
>>> get_structuralresources_category_schemes_agency_resource_version_categories_id(
...     "ISTAC",
...     "TEMAS_CANARIAS",
...     "01.000",
...     "060.060_010.060_010_010"
... )
```

2.3.2 istacpy.structuralresources.classifications

`istacpy.structuralresources.classifications.get_structuralresources_codelist_families(limit=25,
offset=
set=0,
or=
derby='',
query='')`

Get codelist families

This function returns the list of families of classifications

Parameters

- **limit** (*int*) – Results limit. By default `limit = 25`.
- **offset** (*int*) – Displacement. Result from which it is returned. By default `offset = 0`.
- **orderby** (*string*) – Field by which to sort the results.
- **query** (*string*) – Query to filter the results.

Examples

```
>>> get_structuralresources_codelist_families()
```

`istacpy.structuralresources.classifications.get_structuralresources_codelist_families_id(id)`
Get codelist families

This function allows to obtain a family of classifications in particular.

Parameters **id** (*string*) – codelist family identifier

Examples

```
>>> get_structuralresources_codelist_families_id('CODELIST_ID')
```

```
istacpy.structuralresources.classifications.get_structuralresources_codelists(limit=25,  
                           offset=0,  
                           query='',  
                           orderby='')
```

Get codelists

This function allows to obtain the list of classifications.

Parameters

- **limit** (*int*) – Results limit. By default **limit** = 25.
- **offset** (*int*) – Displacement. Result from which it is returned. By default **offset** = 0.
- **query** (*string*) – Query to filter the results.
- **orderby** (*string*) – Field by which to sort the results.

Examples

```
>>> get_structuralresources_codelists()
```

```
istacpy.structuralresources.classifications.get_structuralresources_codelists_agency(agencyid,  
                                     limit=25,  
                                     off-  
                                     set=0,  
                                     query='',  
                                     or-  
                                     derby='')
```

Get codelists agency

This function allows obtaining the list of all the classifications maintained by a certain organization.

Parameters

- **agencyid** (*string*) – Agency identificator.
- **limit** (*int*) – Results limit. By default **limit** = 25.
- **offset** (*int*) – Displacement. Result from which it is returned. By default **offset** = 0.
- **query** (*string*) – Query to filter the results.
- **orderby** (*string*) – Field by which to sort the results.

Examples

```
>>> get_structuralresources_codelists_agency("ISTAC")
>>> get_structuralresources_codelists_agency("ESTAT")
```

```
istacpy.structuralresources.classifications.get_structuralresources_codelists_agency_resource(agencyid,
re-
sour-
ceid,
limit=25,
off-
set=0,
query='',
or-
derby=")
```

Get codelists agency resource

This function allows to obtain all the versions of a classification with a certain identifier and that is also kept by a certain organization.

Parameters

- **agencyid** (*string*) – Agency identifier.
- **resourceid** (*string*) – Resource identifier.
- **limit** (*int*) – Results limit. By default **limit** = 25.
- **offset** (*int*) – Displacement. Result from which it is returned. By default **offset** = 0.
- **query** (*string*) – Query to filter the results.
- **orderby** (*string*) – Field by which to sort the results.

Examples

```
>>> get_structuralresources_codelists_agency_resource("ISTAC", "CL_AREA_ES")
```

```
istacpy.structuralresources.classifications.get_structuralresources_codelists_agency_resource_version(ag
re-
so-
ce
ve
si)
```

Get codelists agency resource version

This function allows you to consult a particular version of a classification.

Parameters

- **agencyid** (*string*) – Agency identifier.
- **resourceid** (*string*) – Resource identifier.
- **version** (*string*) – Specific resource version.

Examples

```
>>> get_structuralresources_codelists_agency_resource_version(  
...     "ISTAC",  
...     "CL_AREA_ES",  
...     "01.000"  
... )
```

```
istacpy.structuralresources.classifications.get_structuralresources_codelists_agency_resource_version(...)
```

Get codelists agency resource version codes

This function allows to consult the codes of a version of a classification. Note that if wildcards are used as `~all` or one of the `limit`, `offset`, `query` or `orderBy` parameters, the list will be automatically paginated.

Parameters

- **agencyid** (*string*) – Agency identifier.
- **resourceid** (*string*) – Resource identifier.
- **version** (*string*) – Specific resource version.
- **limit** (*int*) – Results limit. By default `limit = 25`.
- **offset** (*int*) – Displacement. Result from which it is returned. By default `offset = 0`.
- **query** (*string*) – Query to filter the results.
- **orderby** (*string*) – Field by which to sort the results.
- **openness** (*string*) – Opening established for viewing.
- **order** (*string*) – Order established for visualization.
- **fields** (*string*) – Additional fields that you want to show in the answer.

Examples

```
>>> get_structuralresources_codelists_agency_resource_version_codes(
...     "ISTAC",
...     "CL_AREA_ES",
...     "01.000"
... )
```

`istacpy.structuralresources.classifications.get_structuralresources_codelists_agency_resource_version_codes(...)`

Get codelists agency resource version codes (codeID)

This function allows to consult a specific code of a version of a classification.

Parameters

- **agencyid** (*string*) – Agency identifier.
- **resourceid** (*string*) – Resource identifier.
- **version** (*string*) – Specific resource version.
- **codeid** (*string*) – Code identifier.

Examples

```
>>> get_structuralresources_codelists_agency_resource_version_codes_codeid(
    "ISTAC", "CL_AREA_ES", "01.000", "ES706A01")
```

2.3.3 istacpy.structuralresources.concepts

`istacpy.structuralresources.concepts.get_structuralresources_concept_schemes(limit=25,
 offset=0,
 query='',
 orderby='')`

Get concept schemes

This function returns the content from `/v1.0/conceptschemes`

Parameters

- **limit** (*int*) – Results limit. By default `limit = 25`.
- **offset** (*int*) – Displacement. Result from which it is returned. By default `offset = 0`.
- **query** (*string*) – Query to filter the results.
- **orderby** (*string*) – Field by which to sort the results.

Examples

```
>>> get_structuralresources_concept_schemes()
>>> get_structuralresources_concept_schemes(
...     query="ID EQ 2090",
...     orderby="ID ASC"
... )
```

```
istacpy.structuralresources.concepts.get_structuralresources_concept_schemes_agency(agencyid,
...                                     limit=25,
...                                     off-
...                                     set=0,
...                                     query="",
...                                     or-
...                                     derby="")
```

Get concept schemes agency

This function returns the content from /v1.0/conceptschemes/{agencyID}

Parameters

- **agencyid** (*string*) – Identifier of the agency that publishes.
- **limit** (*int*) – Results limit. By default limit = 25.
- **offset** (*int*) – Displacement. Result from which it is returned. By default offset = 0.
- **query** (*string*) – Query to filter the results.
- **orderby** (*string*) – Field by which to sort the results.

Examples

```
>>> get_structuralresources_concept_schemes_agency("ISTAC")
>>> get_structuralresources_concept_schemes_agency(
...     "ESTAT",
...     query="ID EQ 2090",
...     orderby="ID ASC"
... )
```

```
istacpy.structuralresources.concepts.get_structuralresources_concept_schemes_agency_resource(agencyid,
...                                         re-
...                                         sour-
...                                         ceid,
...                                         limit=25,
...                                         off-
...                                         set=0,
...                                         query="",
...                                         or-
...                                         derby="")
```

Get concept schemes agency resource

This function returns the content from /v1.0/conceptschemes/{agencyID}/{resourceID}

Parameters

- **agencyid** (*string*) – Identifier of the agency that publishes.

- **resourceid** (*string*) – Resource identifier.
- **limit** (*int*) – Results limit. By default **limit** = 25.
- **offset** (*int*) – Displacement. Result from which it is returned. By default **offset** = 0.
- **query** (*string*) – Query to filter the results.
- **orderby** (*string*) – Field by which to sort the results.

Examples

```
>>> get_structuralresources_concept_schemes_agency_resource(
...     agencyid="ISTAC",
...     resourceid="CSM_C00010A_SIE"
... )
```

istacpy.structuralresources.concepts.get_structuralresources_concept_schemes_agency_resource_version(*age-
re-
so-
cei-
ver-
sion*)

Get concept schemes agency resource version

This function returns the content from /v1.0/conceptschemes/{agencyID}/{resourceID}/{version}

Parameters

- **agencyid** (*string*) –
- **resourceid** (*string*) –
- **version** (*string*) –

Examples

```
>>> get_structuralresources_concept_schemes_agency_resource_version(
...     agencyid="ISTAC",
...     resourceid="CSM_C00010A_SIE",
...     version="01.000"
... )
```

istacpy.structuralresources.concepts.get_structuralresources_concept_schemes_agency_resource_version_*con-*

Get concept schemes agency resource version concepts

This function returns the content from /v1.0/conceptschemes/{agencyID}/{resourceID}/{version}/concepts

Parameters

- **agencyid** (*string*) – Identifier of the agency that publishes.
- **resourceid** (*string*) – Resource identifier.
- **version** (*string*) – Specific version of the resource.
- **limit** (*int*) – Results limit. By default **limit** = 25.
- **offset** (*int*) – Displacement. Result from which it is returned. By default **offset** = 0.
- **query** (*string*) – Query to filter the results.
- **orderby** (*string*) – Field by which to sort the results.
- **fields** (*string*) – Additional fields that you want to show in the answer.

Examples

```
>>> get_structuralresources_concept_schemes_agency_resource_version_concepts(  
...     agencyid="ISTAC",  
...     resourceid="CSM_C00010A_SIE",  
...     version="01.000"  
... )
```

```
istacpy.structuralresources.concepts.get_structuralresources_concept_schemes_agency_resource_version_concepts(...)
```

Get concept schemes agency resource version concepts (id)

This function returns the content from /v1.0/conceptschemes/{agencyID}/{resourceID}/{version}/concepts/{conceptID}

Parameters

- **agencyid** (*string*) – Identifier of the agency that publishes.
- **resourceid** (*string*) – Resource identifier.
- **version** (*string*) – Specific version of the resource.
- **conceptid** (*string*) – Concept identifier.

Examples

```
>>> get_structuralresources_concept_schemes_agency_resource_version_concepts_id(
...     agencyid="ISTAC",
...     resourceid="CSM_C00010A_SIE",
...     version="01.000",
...     conceptID="ELECTORES"
... )
```

`istacpy.structuralresources.concepts.get_structuralresources_concept_types()`
Get concept types

This function returns the content from `/v1.0/conceptTypes`

Examples

```
>>> get_structuralresources_concept_types()
```

2.3.4 istacpy.structuralresources.datastructures

`istacpy.structuralresources.datastructures.get_structuralresources_content_constraints(limit=25,
off-
set=0,
query="";
or-
derby="")`

Get content constraints

This function returns the content from `/v1.0/contentConstraints`

Parameters

- **limit** (*int*) – Results limit. By default `limit = 25`.
- **offset** (*int*) – Displacement. Result from which it is returned. By default `offset = 0`.
- **query** (*string*) – Query to filter the results.
- **orderby** (*string*) – Field by which to sort the results.

Examples

```
>>> get_structuralresources_content_constraints()
>>> get_structuralresources_content_constraints(
...     query="ID EQ 2090",
...     orderby="ID ASC"
... )
```

```
istacpy.structuralresources.datastructures.get_structuralresources_content_constraints_agency(agencyid,  
                                         limit=25,  
                                         off-  
                                         set=0,  
                                         query="",  
                                         or-  
                                         derby="")
```

Get content constraints agency

This function returns the content from `/v1.0/contentConstraints/{agencyID}`

Parameters

- **agencyid** (*string*) – Identifier of the agency that publishes.
- **limit** (*int*) – Results limit. By default `limit = 25`.
- **offset** (*int*) – Displacement. Result from which it is returned. By default `offset = 0`.
- **query** (*string*) – Query to filter the results.
- **orderby** (*string*) – Field by which to sort the results.

Examples

```
>>> get_structuralresources_content_constraints_agency("ISTAC")
```

```
istacpy.structuralresources.datastructures.get_structuralresources_content_constraints_agency_resource(
```

Get content constraints agency resource

This function returns the content from `/v1.0/contentConstraints/{agencyID}/{resourceID}`

Parameters

- **agencyid** (*string*) – Identifier of the agency that publishes.
- **resourceid** (*string*) – Resource identifier.
- **limit** (*int*) – Results limit. By default `limit = 25`.
- **offset** (*int*) – Displacement. Result from which it is returned. By default `offset = 0`.
- **query** (*string*) – Query to filter the results.
- **orderby** (*string*) – Field by which to sort the results.

Examples

```
>>> get_structuralresources_content_constraints_agency_resource(
...     "ISTAC",
...     "CSM_C00010A_SIE"
... )
```

istacpy.structuralresources.datastructures.get_structuralresources_content_constraints_agency_resource()

Get content constraints agency resource version

This function returns the content from /v1.0/contentConstraints/{agencyID}/{resourceID}/{version}

Parameters

- **agencyid** (*string*) – Identifier of the agency that publishes.
- **resourceid** (*string*) – Resource identifier.
- **version** (*string*) – Specific version of the resource.

Examples

```
>>> get_structuralresources_content_constraints_agency_resource_version(
...     "ISTAC",
...     "CSM_C00010A_SIE",
...     "01.000"
... )
```

istacpy.structuralresources.datastructures.get_structuralresources_content_constraints_agency_resource_version()

Get content constraints agency resource version regions

This function returns the content from /v1.0/contentConstraints/{agencyID}/{resourceID}/{version}/regions/ {regionCode}

Parameters

- **regioncode** (*string*) –
- **agencyid** (*string*) –
- **resourceid** (*string*) –
- **version** (*string*) –

Examples

```
>>> get_structuralresources_content_constraints_agency_resource_version_regions(
...     "0001",
...     "ISTAC",
...     "CSM_C00010A_SIE",
...     "01.000"
... )
```

```
istacpy.structuralresources.datastructures.get_structuralresources_data_structures(limit=25,
...                                     offset=0,
...                                     set=0,
...                                     query="",
...                                     orderby="")
```

Get data structures

This function returns the content from /v1.0/datastructures

Parameters

- **limit** (*int*) – Results limit. By default **limit** = 25.
- **offset** (*int*) – Displacement. Result from which it is returned. By default **offset** = 0.
- **query** (*string*) – Query to filter the results.
- **orderby** (*string*) – Field by which to sort the results.

Examples

```
>>> get_structuralresources_data_structures()
>>> get_structuralresources_data_structures(
...     query="ID EQ 2090",
...     orderby="ID ASC"
... )
```

```
istacpy.structuralresources.datastructures.get_structuralresources_data_structures_agency(agencyid,
...                                         limit=25,
...                                         offset=0,
...                                         set=0,
...                                         query="",
...                                         orderby="")
```

Get data structures agency

This function returns the content from /v1.0/datastructures/{agencyID}

Parameters

- **agencyid** (*string*) – Identifier of the agency that publishes.
- **limit** (*int*) – Results limit. By default **limit** = 25.
- **offset** (*int*) – Displacement. Result from which it is returned. By default **offset** = 0.
- **query** (*string*) – Query to filter the results.
- **orderby** (*string*) – Field by which to sort the results.

Examples

```
>>> get_structuralresources_data_structures_agency("ISTAC")
```

```
istacpy.structuralresources.datastructures.get_structuralresources_data_structures_agency(agen  
re-  
sour-  
ceid,  
limit=  
off-  
set=0  
query  
or-  
derby
```

Get data structures agency resource

This function returns the content from /v1.0/datastructures/{agencyID}/{resourceID}

Parameters

- **agencyid** (*string*) – Identifier of the agency that publishes.
- **resourceid** (*string*) – Resource identifier.
- **limit** (*int*) – Results limit. By default limit = 25.
- **offset** (*int*) – Displacement. Result from which it is returned. By default offset = 0.
- **query** (*string*) – Query to filter the results.
- **orderby** (*string*) – Field by which to sort the results.

Examples

```
>>> get_structuralresources_data_structures_agency_resource(  
...     "ISTAC",  
...     "DSD_C00010A_00001"  
... )
```

```
istacpy.structuralresources.datastructures.get_structuralresources_data_structures_agency_resource_ver
```

Get data structures agency resource version

This function returns the content from /v1.0/datastructures/{agencyID}/{resourceID}/{version}

Parameters

- **agencyid** (*string*) – Identifier of the agency that publishes.
- **resourceid** (*string*) – Resource identifier.
- **version** (*string*) – Specific version of the resource.

Examples

```
>>> get_structuralresources_data_structures_agency_resource_version(
...     "ISTAC",
...     "DSD_C00010A_00001",
...     "01.001"
... )
```

2.3.5 istacpy.structuralresources.variables

```
istacpy.structuralresources.variables.get_structuralresources_geoinfo(variableid, resourceid,
fields='', limit=25,
offset=0, query='',
orderby='')
```

Get geoinfo

This function returns data from /v1.0/variables/{variableID}/variableelements/{resourceID}/geoinfo

Parameters

- **variableid** (*string*) – Variable identifier.
- **resourceid** (*string*) – Resource identifier.
- **fields** (*string*) – Additional fields that you want to show in the answer.
- **limit** (*int*) – Results limit. By default limit = 25.
- **offset** (*int*) – Displacement. Result from which it is returned. By default offset = 0.
- **query** (*string*) – Query to filter the results.
- **orderby** (*string*) – Field by which to sort the results.

Examples

```
>>> get_structuralresources_geoinfo("VR_TERRITORIO", "MUN_ICOD_VINOS")
```

```
istacpy.structuralresources.variables.get_structuralresources_variable_families(limit=25,
offset=0,
query='',
orderby='')
```

Get variable families

This function returns data from /v1.0/variablefamilies

Parameters

- **limit** (*int*) – Results limit. By default limit = 25.
- **offset** (*int*) – Displacement. Result from which it is returned. By default offset = 0.
- **query** (*string*) – Query to filter the results.
- **orderby** (*string*) – Field by which to sort the results.

Examples

```
>>> get_structuralresources_variable_families()
```

`istacpy.structuralresources.variables.get_structuralresources_variable_families_id(id)`
Get variable families (id)

This function returns data from /v1.0/variablefamilies/{id}

Parameters `id (string)` – Variable family identifier.

Examples

```
>>> get_structuralresources_variable_families_id("VRF_DEMOGRAFICAS")
```

`istacpy.structuralresources.variables.get_structuralresources_variable_families_id_variables(id, limit=25, offset=0, set=0, query='', orderby='')`

Get variable families (id) variables

This function returns data from /v1.0/variablefamilies/{id}/variables

Parameters

- `id (string)` – Variable family identifier.
- `limit (int)` – Results limit. By default `limit = 25`.
- `offset (int)` – Displacement. Result from which it is returned. By default `offset = 0`.
- `query (string)` – Query to filter the results.
- `orderby (string)` – Field by which to sort the results.

Examples

```
>>> get_structuralresources_variable_families_id_variables("VRF_DEMOGRAFICAS")
```

`istacpy.structuralresources.variables.get_structuralresources_variableelements(variableid, limit=25, offset=0, query='', orderby='')`

Get variableelements

This function returns data from /v1.0/variables/{variableID}/variableelements

Parameters

- `variableid (string)` –
- `limit (int)` –
- `offset (int)` – `offset = 0`.

- **query** (*string*) –
- **orderby** (*string*) –

Examples

```
>>> get_structuralresources_variableelements("VR_SEXO")
```

```
istacpy.structuralresources.variables.get_structuralresources_variableelements_resource(variableid,  
                                         re-  
                                         sour-  
                                         ceid)
```

Get variableelements resource

This function returns data from /v1.0/variables/{variableID}/variableelements/{resourceID}

Parameters

- **variableid** (*string*) – Resource identifier.
- **resourceid** (*string*) – Variable identifier.

Examples

```
>>> get_structuralresources_variableelements_resource("VR_SEXO", "FEMALE")
```

```
istacpy.structuralresources.variables.get_structuralresources_variables(limit=25, offset=0,  
                                         query='', orderby='')
```

Get variables

This function returns data from /v1.0/variables

Parameters

- **limit** (*int*) – Results limit. By default limit = 25.
- **offset** (*int*) – Displacement. Result from which it is returned. By default offset = 0.
- **query** (*string*) – Query to filter the results.
- **orderby** (*string*) – Field by which to sort the results.

Examples

```
>>> get_structuralresources_variables()
```

```
istacpy.structuralresources.variables.get_structuralresources_variables_id(id)
```

Get variables (id)

This function returns data from /v1.0/variables/{id}

Parameters **id** (*string*) – Variable identifier.

Examples

```
>>> get_structuralresources_variables_id("VR_SEXO")
```

2.4 Error handling

2.4.1 Custom exceptions

There are a bunch of custom exceptions defined in the package:

```
exception istacpy.exceptions.GranularityNotFoundError(value='', message='given granularity{} is  
not available for this indicator')

exception istacpy.exceptions.IndicatorNotFoundError(value='', message='given indicator{} not found  
on API')

exception istacpy.exceptions.IslandNotFoundError(value='', message='given island{} not found')

exception istacpy.exceptions.IstacPyError(value='', message='')

exception istacpy.exceptions.MeasureNotFoundError(value='', message='given measure{} is not  
available for this indicator')

exception istacpy.exceptions.QueryMalformedError(value='', message='given query{} is malformed or  
not properly written')
```

On the shoulder of giants

Special mention to API requests handling. Behind the scenes, this package uses well-known `requests` package to retrieve data from API. Different errors can happen and they are raised to be captured for the user.

It's important to say that these exceptions will include a custom field called `requested_url` that let's the user to handle the API url.

2.4.2 Debug mode

Debug mode can be enabled using the proper function:

```
from istacpy import services
services.set_debug()
```

Among other side effects, when debug mode is enabled, API urls are displayed when a query is performed:

```
>>> indicators.get_subjects()
https://datos.canarias.es/api/estadisticas/indicators/v1.0/subjects
(('011', 'Territorio y usos del suelo'),
 ('012', 'Medio ambiente'),
 ('021', 'Población'),
 ('022', 'Movimiento natural'),
 ('023', 'Movimientos migratorios'),
 ('031', 'Calidad de vida'),
 ('033', 'Educación'),
 ('036', 'Justicia y seguridad'),
```

(continues on next page)

(continued from previous page)

```
('041', 'Cuentas económicas'),
('042', 'Precios, consumo e inversión'),
('043', 'Empresas y centros de trabajo'),
('051', 'Empleo'),
('061', 'Agricultura, ganadería, pesca y caza'),
('071', 'Industria, energía y agua'),
('072', 'Construcción y vivienda'),
('080', 'SECTOR SERVICIOS'),
('081', 'Comercio'),
('082', 'Hostelería y turismo'),
('083', 'Transporte y comunicaciones'),
('084', 'Servicios financieros, monetarios y seguros'),
('091', 'Administración pública'))
```

Debug can be disabled as well. For that end, you can use the function `services.set_nodebug()`.

PYTHON MODULE INDEX

i

istacpy.exceptions, 51
istacpy.indicators.geographic, 18
istacpy.indicators.indicators, 19
istacpy.indicators.systems, 21
istacpy.statisticalresources.cubes, 27
istacpy.statisticalresources.queries, 25
istacpy.structuralresources.category, 29
istacpy.structuralresources.classifications,
 35
istacpy.structuralresources.concepts, 39
istacpy.structuralresources.datastructures,
 43
istacpy.structuralresources.variables, 48

INDEX

G

get_indicators() (in module `tacpy.indicators.indicators`), 19
get_indicators_code() (in module `tacpy.indicators.indicators`), 20
get_indicators_code_data() (in module `tacpy.indicators.indicators`), 20
get_indicators_geographic_granularities() (in module `istacpy.indicators.geographic`), 18
get_indicators_geographical_values() (in module `istacpy.indicators.geographic`), 18
get_indicators_subjects() (in module `tacpy.indicators.geographic`), 19
get_indicators_systems() (in module `tacpy.indicators.systems`), 21
get_indicators_systems_code() (in module `tacpy.indicators.systems`), 21
get_indicators_systems_code_instances() (in module `istacpy.indicators.systems`), 21
get_indicators_systems_code_instances_code() (in module `istacpy.indicators.systems`), 22
get_indicators_systems_code_instances_code_data() (in module `istacpy.indicators.systems`), 22
get_indicators_time_granularities() (in module `istacpy.indicators.geographic`), 19
get_statisticalresources_datasets() (in module `istacpy.statisticalresources.cubes`), 27
get_statisticalresources_datasets_agency() (in module `istacpy.statisticalresources.cubes`), 27
get_statisticalresources_datasets_agency_resource() (in module `istacpy.statisticalresources.cubes`), 28
get_statisticalresources_datasets_agency_resource_version() (in module `istacpy.statisticalresources.cubes`), 28
get_statisticalresources_queries() (in module `istacpy.statisticalresources.queries`), 25
get_statisticalresources_queries_agency() (in module `istacpy.statisticalresources.queries`), 26
get_statisticalresources_queries_agency_resource() (in module `istacpy.statisticalresources.queries`), 26
get_structuralresources_categorisations() (in module `istacpy.structuralresources.category`), 29
get_structuralresources_categorisations_agency() (in module `tacpy.structuralresources.category`), 30
get_structuralresources_categorisations_agency_resource() (in module `tacpy.structuralresources.category`), 30
get_structuralresources_categorisations_agency_resource_version() (in module `tacpy.structuralresources.category`), 31
get_structuralresources_category_schemes() (in module `tacpy.structuralresources.category`), 31
get_structuralresources_category_schemes_agency() (in module `tacpy.structuralresources.category`), 32
get_structuralresources_category_schemes_agency_resource() (in module `tacpy.structuralresources.category`), 32
get_structuralresources_category_schemes_agency_resource_version() (in module `tacpy.structuralresources.category`), 33
get_structuralresources_codelist_families() (in module `tacpy.structuralresources.classifications`), 35
get_structuralresources_codelist_families_id() (in module `tacpy.structuralresources.classifications`), 35
get_structuralresources_codelists() (in module `istacpy.structuralresources.classifications`), 36
get_structuralresources_codelists_agency() (in module `istacpy.structuralresources.classifications`), 36

```

(in module is- tacpy.structuralresources.datastructures),
  tacpy.structuralresources.classifications), 45
36           get_structuralresources_content_constraints_agency_resource()
(in module is- tacpy.structuralresources.datastructures),
  tacpy.structuralresources.classifications), 45
37           get_structuralresources_data_structures()
get_structuralresources_codelists_agency_resource_version() module is-
  (in module is- tacpy.structuralresources.datastructures),
    tacpy.structuralresources.classifications), 46
37           get_structuralresources_data_structures_agency()
get_structuralresources_codelists_agency_resource_version_codes() module is-
  (in module is- tacpy.structuralresources.datastructures),
    tacpy.structuralresources.classifications), 46
38           get_structuralresources_data_structures_agency_resource()
get_structuralresources_codelists_agency_resource_version_codes_code_id() module is-
  (in module is- tacpy.structuralresources.datastructures),
    tacpy.structuralresources.classifications), 47
39           get_structuralresources_data_structures_agency_resource_version()
get_structuralresources_concept_schemes() (in module is- tacpy.structuralresources.concepts),
  tacpy.structuralresources.concepts), 47
39           get_structuralresources_geoinfo() (in module is-
  (in module is- tacpy.structuralresources.variables), 48
  tacpy.structuralresources.concepts), 40           get_structuralresources_variable_families()
get_structuralresources_concept_schemes_agency_resource_id() module is-
  (in module is- tacpy.structuralresources.variables), 48
  tacpy.structuralresources.concepts), 40           get_structuralresources_variable_families_id()
get_structuralresources_concept_schemes_agency_resource_id_version() module is-
  (in module is- tacpy.structuralresources.variables), 49
  tacpy.structuralresources.concepts), 41           get_structuralresources_variable_families_id_variables()
get_structuralresources_concept_schemes_agency_resource_id_version_concept_id() module is-
  (in module is- tacpy.structuralresources.variables), 49
  tacpy.structuralresources.concepts), 41           get_structuralresources_variable_elements()
get_structuralresources_concept_schemes_agency_resource_id_version_concept_id() module is-
  (in module is- tacpy.structuralresources.variables), 49
  tacpy.structuralresources.concepts), 42           get_structuralresources_variable_elements_resource()
get_structuralresources_concept_types() (in module is- tacpy.structuralresources.variables), 50
  tacpy.structuralresources.concepts), 43           get_structuralresources_variables() (in module
  is- istacpy.structuralresources.variables), 50
get_structuralresources_content_constraints() (in module is- get_structuralresources_variables_id() (in
  tacpy.structuralresources.datastructures), 43           module is- istacpy.structuralresources.variables),
  50           get_structuralresources_variables_id()
get_structuralresources_content_constraints_agency_resource() | GrayParityNotFoundError, 51
  (in module is- tacpy.structuralresources.datastructures), 43           IndicatorNotFoundError, 51
  43           get_structuralresources_content_constraints_agency_resource()
get_structuralresources_content_constraints_agency_resource() | GrayParityNotFoundError, 51
  (in module is- istacpy.exceptions
  tacpy.structuralresources.datastructures), 44           module, 51
  44           istacpy.indicators.geographic
get_structuralresources_content_constraints_agency_response_version() | ResponseVersionError
  (in module is- istacpy.indicators.indicators

```

```
    module, 19
istacpy.indicators.systems
    module, 21
istacpy.statisticalresources.cubes
    module, 27
istacpy.statisticalresources.queries
    module, 25
istacpy.structuralresources.category
    module, 29
istacpy.structuralresources.classifications
    module, 35
istacpy.structuralresources.concepts
    module, 39
istacpy.structuralresources.datastructures
    module, 43
istacpy.structuralresources.variables
    module, 48
IstacPyError, 51
```

M

```
MeasureNotFoundError, 51
module
    istacpy.exceptions, 51
    istacpy.indicators.geographic, 18
    istacpy.indicators.indicators, 19
    istacpy.indicators.systems, 21
    istacpy.statisticalresources.cubes, 27
    istacpy.statisticalresources.queries, 25
    istacpy.structuralresources.category, 29
    istacpy.structuralresources.classifications,
        35
    istacpy.structuralresources.concepts, 39
    istacpy.structuralresources.datastructures,
        43
    istacpy.structuralresources.variables, 48
```

Q

```
QueryMalformedError, 51
```